

DSD55-HE2

This 55" display especially designed for creative and innovative retailers looking for an eye catching display. The DSD55-HE2 is ideal for long-term use due to the advanced thermal control and strong exterior.



The all-around 55" display

Display Orientation	Portrait / Landscape
Green Compliance	RoHS : Yes
Internal Speaker	Option
IR remote control	Yes
Keypad	Yes
Life time	50,000 Hrs
Operating Temperature	0~40°C
Operating Humidity	10~80% RH max
OSD display	Yes
Storage Temperature	-20° to 60°
Storage Humidity	10~80%RH max
Tempered Glass	Option

Connectivity

HDMI : in x2, VGA : in x2
 RS232 : in x1/out x1, Audio : in x2/out x1
 External Speaker : R/L 8Wx2

Mechanical Spec.

VESA Mount:500x400/300x400
 Screw Insertion of VESA mount(Max.) : 8.2mm
 Color:Black
 Weight((Net/Gross): 28Kg / 36Kg
 Set Dimension (LxHxD):1239x 710x 49 mm
 Package Dimension (LxHxD):1470x 944x 285 mm
 Bezel width:11.8 mm
 AC inlet/outlet :Input x1/ Output x1

Package Contents

AC power cable : Yes
 Remote controller : Yes
 Battery : CR2025
 VESA Mount screw x4 pcs

Panel

Diagonal size : 55 inch
 Type : AMVA
 Resolution : 1920x1080
 Pixels Pitch (H x W) : 0.21x0.63
 Brightness (typ.) : 450 nits
 Contrast Ratio : 4000:1
 Viewing Angel (H/W) : 178/178
 Response Time (G-to-G) : 6.5 ms
 Color/gray scale : 1073M/10bits
 Aspect ratio : 16:9
 Frequency : 60Hz
 Surface Treatment :AG,3H

Power

Power Consumption (Max.) : 120 W
 Power Consumption at Stand-by(Max.) : 1.5 W
 Power Input : AC 100~240V AC 50/60Hz

Regulation and Standard Compliance

FCC, UL, CE, CB, BSMI

Special features

Narrow Bezel 11.8mm, Fanless
 Thermal Alarm & Protection

- Narrow Bezel
- Metal Framework
- Fanless
- Thermal Alarm & Protection
- RS232 remote control API utility support

